



Reactor Neo Aluminum Plates

Plate size	Riedell boot size	Plate length in mm	Wheelbase in mm	Toe length* in mm	Heel length** in mm	Plate length in inches	Wheelbase in inches	Plate weight each / pair in ounces	Plate assembly weight*** each / pair in ounces
3	3, 3 1/2	220	134	60	26	8 2/3	5 1/4	6.81 / 13.62	16.22 / 32.44
4	4, 4 1/2	230	144	60	26	9 1/10	5 2/3	6.98 / 13.96	16.40 / 32.80
5	5, 5 1/2	236	150	60	26	9 3/10	5 9/10	7.16 / 14.32	16.58 / 33.16
6	6, 6 1/2	244	156	62	26	9 3/5	6 1/8	7.34 / 14.68	16.75 / 33.50
7	7, 7 1/2	252	162	64	26	9 9/10	6 3/8	7.51 / 15.02	16.93 / 33.86
8	8, 8 1/2	260	168	66	26	10 1/4	6 5/8	7.69 / 15.38	17.11 / 34.22
9	9, 9 1/2	268	174	68	26	10 11/20	6 17/20	7.87 / 15.74	17.28 / 34.56
10	10, 10 1/2	276	180	70	26	10 17/20	7 1/10	8.04 / 16.08	17.46 / 34.92
11	11, 11 1/2	284	186	72	26	11 1/5	7 1/3	8.25 / 16.50	17.67 / 35.34
12	12, 12 1/2	292	192	74	26	11 1/2	7 9/16	8.50 / 17.00	17.92 / 35.84
13	13	300	198	76	26	11 4/5	7 4/5	8.75 / 17.50	18.17 / 36.34

*Toe length is distance from center of front axle to front end of plate

**Heel length is distance from center of back axle to back end of plate

***Plate assembly includes kingpins, trucks, cushions, cushion cups, lock nuts

This chart is a guide - recommendations from the manufacturer. Plate size and mounting can vary for skaters. Skates mounted at Riedell will use this guide unless otherwise specified.